

COMPRESSOR FILTER HELAPET

AIR DISC FILTER 0,2 μ

Leaflet F-22-00-UK



**Fluxa
Filtri
S.p.A.**

V.le A. De Gasperi, 88/B-20017 Mazzo di Rho (MI)
Tel. 0293959.1 (15 linee)
Fax 0293959.400-440-470
e-mail: info@fluxafiltri.com - www.fluxafiltri.com

Agent for South Italy:
Sire srl.- Via Sannio, 9 - 80146 Napoli
Tel. 0817349254 – 0817349310
Fax 0817349317

Technical specification

Air disc filter 0,2 micron
for compressor



MATERIAL OF CONSTRUCTION

- Membrane: PTFE da 0,2 micron
- Support: polypropylene
- Assembling procedure: thermal
- Filter housing: polypropylene
- Diameter: 53 mm.

TECHNICAL FEATURE

- Max. working pressure 4 bar @ 20°C
- Max. Δp 3 bar @ 20°C
- Flow rate 23 l/m. @ 700 mbar
- Autoclave sterilization 121°C per 20'; max. 135°C ri for 20' (once)
- Biological compatibility according to USP class VI standard for plastic
- Traceability: lot number on every single filter
- Produced in clean room accord dimoto CGMP
- Filtration area 14,5 cm²

