HY-PRO
FILTRATION

DFE Filter Element Upgrades

Gearbox Filtration

Contamination Solutions for Power Generation

Varnish Removal & Prevention

Water Removal & Particulate Control

FLUXA
Fluxa Filtri S.p.A.
V.le A.De Gasperi, 88/B - 20017 Mazzo di Rho (MI) Italy
Tel. +39 02.93959.1 (15 linee) Fax +39 02.93959.400/440/470
e-mail: info@fluxafiltri.com - www.fluxafiltri.com

V-22-00-UK

Fluid Contamination Under Control With Hy-Pro

Hy-Pro DFE Rated Filter Elements

Turbine Oil Conditioner
Coalesce & Particulate
Element Upgrades

Non-Spark Discarge Element
Upgrades Prevent Fluid
Degradation & Extend Additive Life

DFE Rated Filter Elements
Upgrades for All Filter OEMs

Hydraulic & Lube Filter Element Upgrades

Compressor, Gearbox, Feed Pump & Seal Oil Contamination Solutions

Innovative Products
Support & Solutions

FCL - Filter Cart for
High Viscosity Fluid
Conditioning & Transfer

DFN - Seal Oil & BFP
Filtration Upgrades

FSL - Side Loop
Gearbox Filtration

FPL - Filter Panel Ideal
for Compressors

HY-PRO
FILTRATION

Filtration's Total System Cleanliness Approach
& fluid Contamination Equipment

Vacuum Dehydrator-Removes Free & Dissolved Water, Low ISO Codes

COT– Turbine Oil Coalesce Skid Rapidly Controls Water & Particulate

SVR– Soluble Varnish Removal System Stops Fail to Start and Unit Trips

Off-Line Lube Oil Conditioning Skids

Phosphate Ester Fluid Maintenance (EHC)

Innovative Products Support & Solutions

Hy-Dry Desiccant Reservoir Breathers

TMR– Maintains Phosphate Ester Water Levels Below 300ppm

ICB-Dry Ion Charge Bonding Acid Scavenging Elements for Phosphate Ester EHC Systems

ECR– Electrostatic Removes Thermal Degredation Sub-Micron Particles

HY-PRO FILTRATION

Cleaner Fluid…. Longer Component & Fluid Life… More Uptime!

ROLLER CONTACT BEARING

Current ISO Code	Target ISO Code	Target ISO Code	Target ISO Code	Target ISO Code
	2 x Life	3 x Life	4 x Life	5 x Life
26/24/21	22/20/17	20/18/15	19/17/14	17/15/12
25/23/20	21/19/16	19/17/14	15/15/12	16/14/11
22/22/19	20/18/15	16/16/13	16/14/11	15/13/10
23/21/18	19/17/14	17/15/12	15/13/10	14/12/9
22/20/17	18/16/13	16/14/11	15/13/10	13/11/8
21/19/16	17/15/12	15/13/10	13/11/8	-
20/18/15	16/14/11	14/12/9	-	-
19/17/14	15/13/10	13/11/8	-	-
18/16/13	14/12/9	-	-	-
17/15/12	13/11/8	-	-	-
16/14/11	13/11/8	-	-	-
15/13/10	13/11/8	-	-	-
14/12/9	13/11/8	-	-	-

HYDRAULIC COMPONENT

Current ISO Code	Target ISO Code	Target ISO Code	Target ISO Code	Target ISO Code
	2 x Life	3 x Life	4 x Life	5 x Life
26/24/21	23/21/18	22/20/17	21/19/16	21/19/15
25/23/20	22/20/17	21/19/16	20/18/15	19/17/14
25/22/19	21/19/16	20/18/15	19/17/14	18/16/13
23/21/18	20/18/15	19/17/14	18/16/13	17/15/12
22/20/17	19/17/14	18/16/13	17/15/12	16/14/11
21/19/16	18/16/13	17/15/12	16/14/11	15/13/10
20/18/15	17/15/12	16/14/11	15/13/10	14/12/9
19/17/14	16/14/11	15/13/10	14/12/9	14/12/8
18/16/13	15/13/10	14/12/9	13/11/8	-
17/15/12	14/12/9	13/11/8	-	-
16/14/11	13/11/8	-	-	-
15/13/10	13/11/8	-	-	-
14/12/9	13/11/8	-	-	-

Succeed with a Total Systems Cleanliness Approach

Developing a Total System Cleanliness approach to control contamination and care for fluids from arrival to disposal will ultimately result in more reliable plant operation and save money. Several steps to achieve Total Systems Cleanliness include: evaluate and survey all hydraulic and lubrification systems, establish a baseline and target fluid cleanliness for each system, filter all new fluids upon arrival and during transfer, seal all reservoirs and bulk tanks, install high quality particulate and desiccant breathers, enhance air and liquid filtration on existing systems, wherever suitable use portable or permanent off-line filtration to enhance existing filtration, improve bulk oil storage and handling during transfer, remove water and make a commitment to fluid cleanliness.

The visible cost of proper contamination control and Total Systems Cleanlisess is less than 3% of the total cost of contamination when not kept under control. Keep your head above the surface and avoid the resource draining costs associated with fluid contamination issues including:

- Down Time and Lost Production
- Component Repair / Replacement
- Reduced Useful Fluid Life
- Wasted Materials and Supplies
- Root Cause Analysis Meetings
- Maintenance Labor Costs
- Unreliable Machine Performance
- Wasted Time and Energy



HY-PRO FILTRATION

FLUXA

Fluxa Filtri S.p.A.

V.le A.De Gasperi, 88/B - 20017 Mazzo di Rho (MI) Italy
Tel. +39 02.93959.1 (15 linee) Fax +39 02.93959.400/440/470
e-mail: info@fluxafiltri.com - www.fluxafiltri.com

V-22-00-UK